

NON-Hazardous Substance, NON-Dangerous Goods

1. MATERIAL AND SUPPLY COMPANY IDENTIFICATION

Product name: 636-LINE BERGER SOLARSCREEN LOW SHEEN

Synonyms:	Product Code	Bar Code
BERGER PREMIUM SOLARSCREEN EXT LS WHITE 10L	63670016-10L	9300611448422
BERGER PREMIUM SOLARSCREEN EXT LS WHITE 15L	63670016-15L	9300611448415
BERGER PREMIUM SOLARSCREEN EXT LS WHITE 1L	63670016-1L	9300611448453
BERGER PREMIUM SOLARSCREEN EXT LS WHITE 2L	63670016-2L	9300611448446
BERGER PREMIUM SOLARSCREEN EXT LS WHITE 4L	63670016-4L	9300611448439
BERGER PREMIUM SOLARSCREEN EXT LS WHITE 6L	63670016-6L	9300611498779
BERGER PREMIUM SOLARSCREEN EXT LS RED 1L	63670022-1L	9300611508713
BERGER PREMIUM SOLARSCREEN EXT LS RED 4L	63670022-4L	9300611508751
BERGER PREMIUM SOLARSCREEN EXT LS BLUE 1L	63670023-1L	9300611508720
BERGER PREMIUM SOLARSCREEN EXT LS BLUE 4L	63670023-4L	9300611508768
BERGER PREMIUM SOLARSCREEN EXT LS YELLOW 1L	63670024-1L	9300611508737
BERGER PREMIUM SOLARSCREEN EXT LS YELLOW 4L	63670024-4L	9300611508775
BERGER PREMIUM SOLARSCREEN EXT LS EBTB 15L	63670025-15L	9300611536891
BERGER PREMIUM SOLARSCREEN EXT LS EBTB 1L	63670025-1L	9300611508706
BERGER PREMIUM SOLARSCREEN EXT LS EBTB 4L	63670025-4L	9300611508744
BERGER PREMIUM SOLARSCREEN EXT LS DEEP 10L	63670026-10L	9300611448262
BERGER PREMIUM SOLARSCREEN EXT LS DEEP 1L	63670026-1L	9300611448286
BERGER PREMIUM SOLARSCREEN EXT LS DEEP 4L	63670026-4L	9300611448279
BERGER PREMIUM SOLARSCREEN EXT LS AMBER 1L	63670027-1L	9300611449061
BERGER PREMIUM SOLARSCREEN EXT LS AMBER 4L	63670027-4L	9300611448200
BERGER PREMIUM SOLARSCREEN EXT LS BRIGHT 1L	63670028-1L	9300611448224
BERGER PREMIUM SOLARSCREEN EXT LS BRIGHT 4L	63670028-4L	9300611448217
BERGER PREMIUM SOLARSCREEN EXT LS BRUN GREE		
	63670029-1L	9300611448170
BERGER PREMIUM SOLARSCREEN EXT LS BRUN GREEN 4L		
	63670029-4L	9300611448163
BERGER PREMIUM SOLARSCREEN EXT LS EDTB 10L	63670030-10L	9300611448231
BERGER PREMIUM SOLARSCREEN EXT LS EDTB 1L	63670030-1L	9300611448255
BERGER PREMIUM SOLARSCREEN EXT LS EDTB 4L	63670030-4L	9300611448248
BERGER PREMIUM SOLARSCREEN EXT LS INDIAN RED 1L		
	63670031-1L	9300611448194
BERGER PREMIUM SOLARSCREEN EXT LS INDIAN RED		
	63670031-4L	9300611448187
BERGER PREMIUM SOLARSCREEN EXT LS MISS BROWN 1L		
	63670032-1L	9300611448156
BERGER PREMIUM SOLARSCREEN EXT LS MISS BROWN 4L		
	63670032-4L	9300611448149

Recommended use: Surface coating. Applied by brush, roller or spray.

Supplier: Dulux Australia, a division of

DuluxGroup (Australia) Pty Ltd

ABN: 67 000 049 427

Street Address: 1956 Dandenong Road

Clayton VIC 3168

Australia

Telephone: 13 25 25

Product name: 636-LINE BERGER SOLARSCREEN LOW SHEEN SDS No: DLXGHSEN000236

Issued: 5 May 2015 Version: 5.0 Page: 1 of 6



Emergency telephone number: Australia – 1800 033 111 New Zealand – 0800 734 607

2. HAZARDS IDENTIFICATION

Based on available information, this material is not classified as hazardous according to criteria of Safe Work Australia.

Poisons Schedule (Aust): Not applicable

DANGEROUS GOODS CLASSIFICATION

Not classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".

3. COMPOSITION INFORMATION

CHEMICAL ENTITY CAS NO. PROPORTION

Ingredients determined to be non-hazardous - 100%

4. FIRST AID MEASURES

If poisoning occurs, contact a doctor or Poisons Information Centre (Phone Australia 131 126, New Zealand 0800 764 766).

Inhalation: Remove victim from exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. Seek medical advice if effects persist.

Skin contact: If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. If swelling, redness, blistering or irritation occurs seek medical assistance.

Eye contact: If in eyes wash out immediately with water. In all cases of eye contamination it is a sensible precaution to seek medical advice.

Ingestion: Rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water to drink. If vomiting occurs give further water. Seek medical advice.

PPE for First Aiders: Wear overalls, safety glasses and impervious gloves. Available information suggests that gloves made from nitrile rubber should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

Notes to physician: Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Hazchem Code: Not applicable.

Product name: 636-LINE BERGER SOLARSCREEN LOW SHEEN SDS No: DLXGHSEN000236

Issued: 5 May 2015 Version: 5.0 Page: 2 of 6



Suitable extinguishing media: If material is involved in a fire use water fog (or if unavailable fine water spray), foam, dry agent (carbon dioxide, dry chemical powder).

Specific hazards: Non-combustible material.

Fire fighting further advice: Not combustible, however following evaporation of aqueous component residual material can burn if ignited. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion.

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILLS

Wear protective equipment to prevent skin and eye contamination. Wipe up with absorbent (clean rag or paper towels). Allow absorbent to dry before disposing with normal household garbage.

LARGE SPILLS

Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contamination and the inhalation of vapours. Work up wind or increase ventilation. Contain - prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Collect and seal in properly labelled containers or drums for disposal. If contamination of sewers or waterways has occurred advise local emergency services.

Dangerous Goods - Initial Emergency Response Guide No: Not applicable.

7. HANDLING AND STORAGE

Handling: Avoid skin and eye contact and inhalation of vapour, mist or aerosols.

Storage: Store in a cool, dry, well-ventilated place and out of direct sunlight. Store away from incompatible materials described in Section 10. Keep containers closed when not in use - check regularly for leaks.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

National occupational exposure limits: No value assigned for this specific material by Safe Work Australia or Department of Labour New Zealand.

Biological Limit Values: As per the "National Model Regulations for the Control of Workplace Hazardous Substances (Safe Work Australia)" the ingredients in this material do not have a Biological Limit Allocated.

Engineering measures: Use only in well ventilated areas. Keep containers closed when not in use.

Personal protection equipment: B: OVERALLS, SAFETY SHOES, SAFETY GLASSES, GLOVES.

Wear overalls, safety glasses and impervious gloves. Available information suggests that gloves made from nitrile rubber should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or reusing.

If risk of inhalation of exists, wear organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716.

Product name: 636-LINE BERGER SOLARSCREEN LOW SHEEN SDS No: DLXGHSEN000236

Issued: 5 May 2015 Version: 5.0 Page: 3 of 6



Hygiene measures: When using do not eat, drink or smoke. Wash hands prior to eating, drinking or smoking. Avoid skin and eye contact and inhalation of vapour, mist or aerosols. Ensure that eyewash stations and safety showers are close to the workstation location.

9. PHYSICAL AND CHEMICAL PROPERTIES

Form / Colour / Odour: Coloured, viscous liquid with a mild characteristic odour.

Solubility: Miscible with water.

Specific Gravity (20 °C): 1.0 - 1.9Relative Vapour Density (air=1): >1 Vapour Pressure (20 °C): N Av Flash Point (°C): N App Flammability Limits (%): N App N App **Autoignition Temperature (°C):** Melting Point/Range (°C): N Av **Boiling Point/Range (°C):** Approx. 100 % Volatile by Volume: N Av

% Volatile by Volume: N Av pH: N Av Viscosity: N Av

(Typical values only - consult specification sheet)

N Av = Not available

N App = Not applicable

10. STABILITY AND REACTIVITY

Reactivity: No reactivity hazards are known for the material.

Chemical stability: This material is thermally stable when stored and used as directed.

Hazardous reactions: No known hazardous reactions.

Conditions to avoid: Elevated temperatures.

Incompatible materials: Oxidising agents.

Hazardous decomposition products: Oxides of carbon and nitrogen, smoke and other toxic fumes.

11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Inhalation: Where this material is used in a poorly ventilated area, at elevated temperatures or in confined spaces, vapour may cause irritation to mucous membranes and respiratory tract, headache and nausea.

Skin contact: Contact with skin may result in irritation.

Ingestion: No adverse effects expected however large amounts may cause nausea and vomiting.

Eye contact: May be an eye irritant.

Product name: 636-LINE BERGER SOLARSCREEN LOW SHEEN SDS No: DLXGHSEN000236

Issued: 5 May 2015 Version: 5.0 Page: 4 of 6



Acute toxicity

Inhalation: This material has been classified as non-hazardous.

Skin contact: This material has been classified as non-hazardous.

Ingestion: This material has been classified as non-hazardous.

Corrosion/Irritancy: Eye: this material has been classified as not corrosive or irritating to eyes.

Skin: this material has been classified as not corrosive or irritating to skin.

Sensitisation: Inhalation: this material has been classified as not a respiratory sensitiser.

Skin: this material has been classified as not a skin sensitiser.

Aspiration hazard: This material has been classified as non-hazardous.

Specific target organ toxicity (single exposure): This material has been classified as non-hazardous.

Chronic Toxicity

Mutagenicity: This material has been classified as non-hazardous.

Carcinogenicity: This material has been classified as non-hazardous.

Reproductive toxicity (including via lactation): This material has been classified as non-hazardous.

Specific target organ toxicity (repeat exposure): This material has been classified as non-hazardous.

12. ECOLOGICAL INFORMATION

Avoid contaminating waterways.

Acute aquatic hazard: No information is available to complete an assessment.

Long-term aquatic hazard: No information is available to complete an assessment.

Ecotoxicity: No information available.

Persistence and degradability: No information available.

Bioaccumulative potential: No information available.

Mobility: No information available.

13. DISPOSAL CONSIDERATIONS

Persons conducting disposal, recycling or reclamation activities should ensure that appropriate personal protection equipment is used, see "Section 8. Exposure Controls and Personal Protection" of this SDS.

If possible material and its container should be recycled. If material or container cannot be recycled, dispose in accordance with local, regional, national and international Regulations.

Product name: 636-LINE BERGER SOLARSCREEN LOW SHEEN SDS No: DLXGHSEN000236

Issued: 5 May 2015 Version: 5.0 Page: 5 of 6



14. TRANSPORT INFORMATION

ROAD AND RAIL TRANSPORT

Not classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".

MARINE TRANSPORT

Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

AIR TRANSPORT

Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air

15. REGULATORY INFORMATION

This material is not subject to the following international agreements:

Montreal Protocol (Ozone depleting substances)
The Stockholm Convention (Persistent Organic Pollutants)
The Rotterdam Convention (Prior Informed Consent)
Basel Convention (Hazardous Waste)
International Convention for the Prevention of Pollution from Ships (MARPOL)

This material/constituent(s) is covered by the following requirements:

 All the constituents of this material are listed on the Australian Inventory of Chemical Substances (AICS).

16. OTHER INFORMATION

Literary reference

This Safety Data Sheet has been prepared by Chemical Data Services Pty Ltd (chemdata.com.au) on behalf of its client.

Reason(s) For Issue: Five year update. Format change. Minor Text Changes.

Safety Data Sheets are updated frequently. Please ensure that you have a current copy.

This SDS summarises at the date of issue our best knowledge of the health and safety hazard information of the product, and in particular how to safely handle and use the product in the workplace. Since DuluxGroup (Australia) Pty Ltd and DuluxGroup (New Zealand) Pty Ltd cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, review this SDS in the context of how the user intends to handle and use the product in the workplace.

If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact this company.

Our responsibility for product as sold is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available upon request.

Product name: 636-LINE BERGER SOLARSCREEN LOW SHEEN SDS No: DLXGHSEN000236

Issued: 5 May 2015 Version: 5.0 Page: 6 of 6