

AUBE00049 Berger Everlast Interior Low Sheen

Introduction

Part A
668-line

Description and Image

Berger Everlast Low Sheen creates a beautiful and washable finish that is built to last in your home. Featuring low VOC, low odour BreatheEasy® technology, Berger Everlast allows you to move back into your home sooner. Its smooth finish is tough, hardwearing, and designed to last.



Features and Benefits

- Water based
- Excellent stain resistance
- Excellent mould resistance
- Low odour, low VOC - BreatheEasy (R)
- Beautiful smooth and washable finish
- Tough and hardwearing






Uses

Berger Everlast is ideal for all interior broadwall areas.

✓ Interior

Performance Guide

Weather Designed for interior use only.	Salt NA
Heat Resistance Softens and sticks to other painted surfaces over 70°	Water Suitable for use in wet areas
Solvent Sensitive to aromatic hydrocarbons and alcohols	Abrasion Good wet and dry burnish resistance and stain removal
Acid NA	Alkali NA

Typical Properties			
Gloss Level Low Sheen	Thinner Water		
Colour Machine tinted to a wide range of colours from white, deep, extra deep, extra bright and coloured bases.			
Components 1	Number of Coats 2		
Toxicity NA	V.O.C. Level < 5g/L untinted		
Shelf Life 2 years	Meets GBCA V.O.C. Requirements? Yes Total Volatile Organic Content (TVOC) values are calculated in accordance to the stated methodology within Green Star Technical Manuals. The TVOC content is theoretically calculated as the sum total of the known VOC values of the product's raw material components. These materials include the base paint plus additional low VOC tinter required for non-factory packaged colours.		
Touch Dry 30 minutes			
Clean Up  Water			
Clean Up Description Clean all equipment immediately with water.			
Application Methods  Air Spray  Airless Spray  Brush  Roller			
Application Conditions	Solids by Volume <input type="text" value="40"/>		
	Min	Max	Recommended
Wet Film Per Coat (microns)	<input type="text"/>	<input type="text"/>	<input type="text" value="62.5"/>
Dry Film Per Coat (microns)	<input type="text"/>	<input type="text"/>	<input type="text" value="25"/>
Recoat Time (min/hours)	<input type="text" value="2 hr"/>	<input type="text" value="Indefinite"/>	<input type="text" value="2 hr"/>
Theoretical Spread Rate (m ² /L)	<input type="text"/>	<input type="text"/>	<input type="text" value="16.00"/>

Application Guide

Surface Preparation

- Do not apply paint if the temperature is below 10°C or likely to fall below 10°C during the drying period.

Preparation

Scrape off loose and flaking paint. Wash with sugar soap and rinse clean. Fill nail holes, cracks, etc. with a suitable filler. Sand smooth and dust down. Sand gloss and semi gloss surfaces to a matt finish before painting.

Previously painted surface - Undercoat

Not required.

Bare plasterboard, cement or brick - Undercoat

Berger Triple Prep® Acrylic Sealer Undercoat.

Bare set plaster or powdery surfaces - Undercoat

Berger Triple Prep Oil Based.

Bare timber - Undercoat

Berger Triple Prep Acrylic.

Over enamel paint - Undercoat

Not required.

Application Procedure and Equipment

Stir well before use with a broad, flat stirrer. Under hot weather conditions use a hot weather additive or thin using 100mL of clean water per litre if required.

Application

After following the preparation guide, apply with brush, spray or medium nap roller (9-12mm). Application should be in standard temperature conditions (above 10°C and below 30°C). Apply 2 coats of Berger Everlast Low Sheen. To achieve the best finish, ensure the paint is not worked excessively. When coating over some dark colours an extra coat may be required. Thinning not usually required. If necessary thin with up to 100 ml of water per litre to ease application.

Airless/Conventional Spray: Suitable for application by all standard spray equipment. For conventional spraying up to 125 ml per litre of water may be added to aid atomisation. For airless spraying up to 30 ml per litre of water may be added to aid atomisation.

Care of new paintwork

Avoid exposure to steam and condensation for 48 hours after painting. May be cleaned with a wet cloth and detergent after 7 days.

Drying time

Drying times on a day of around 25°C. Touch dry in 30 minutes. Re-coat in 2 hours. Under cooler or humid conditions allow longer times.

Health and Safety

SDS Number
DLXGHSEN002705

SDS Link
[View SDS Link](#)

Personal Equipment
Wear eye protection and when spraying wear a dust mask.

Please refer to SDS Link. In case of emergency, please call 1800 220 770.

Transport and Storage	
Pack A 668-LINE	
Size:	Weight:
1 Litre 2 Litre 4 Litre 10 Litre 15 Litre	1.5Kg 3.5Kg 5.6Kg 14.0Kg 21.7Kg
Flash Point NA	UN Number NA

Disclaimer

This Data Sheet is copyright to DuluxGroup (Australia) Pty Ltd and/or DuluxGroup (New Zealand) Pty Ltd (collectively, 'Dulux'). It may not be varied or altered without the prior written consent of Dulux, and if it is, Dulux has no responsibility or liability for those variations.

Unless Dulux has provided you with a customised, project-specific specification, this Data Sheet does not represent that any particular product or product system will be suitable for your project.

Any information provided in this Data Sheet is given in good faith and is believed by Dulux to be correct at the time of publication. Products and coating systems can be expected to perform as indicated in this Data Sheet, provided the substrate is in good condition, the coatings are applied by a suitably experienced and skilled applicator, and the preparation, application and maintenance is followed strictly as set out in this Data Sheet, and as recommended on the applicable Safety Data Sheets for the relevant products, available from www.duspecplus.com.au. Climatic conditions at application time can affect product suitability and performance.

The correct colour or colour match is the responsibility of the applicator. Colours will change over time and Dulux does not guarantee that the same colour newly mixed will match a colour applied earlier which has been subjected to weathering or other change elements. No product colour is guaranteed against colour change.

Where any liability of Dulux in respect of this Data Sheet cannot by law be excluded, Dulux's liability is limited, as permitted by law and at Dulux's option, to resupply of the relevant products or services or to reimbursing the cost of those products or services.

WHERE LEAD MAY BE PRESENT: The asset manager is responsible for verifying the presence of lead and determining whether to remove or encapsulate the lead. If lead is present, the work must be done in strict accordance with AS 4361 Parts 1 and 2 and Worksafe Australia guidelines.