

## AUBE00018 Berger Premium Ceiling Flat

### Introduction

Part A  
671-70020

### Description and Image

**Berger Premium Ceiling Flat** is an interior flat white water based paint with outstanding hiding power for use on ceilings.

### Features and Benefits

- Water based
- Excellent opacity
- Flat finish
- Same day recoat, easy clean up and low odour
- Great covering power
- Hides plastering imperfections - ideal for low ceilings

### Uses

Berger Premium Ceiling Flat is specifically designed to minimise the difficulties in painting ceilings and provide a flat finish.

✓ **Interior**

### Precautions and Limitations

**All preparation and painting must conform to AS2311: The Painting of Buildings.**

Do not exceed recommended spreading rate. Avoid exposure to steam and condensation for 48 hours after application. Although the film is dry to touch in 20 minutes, allow 7 days for the film to fully cure before lightly cleaning with a sponge wet with detergent solution. Do not paint at temperatures below 10 degrees Celsius or when the temperature of surface may fall below 10 degrees Celsius during the drying period.

### Performance Guide

Weather <b>Not suitable for exterior application.</b>	Salt <b>NA</b>
Heat Resistance <b>Up to 60C</b>	Water <b>For interior use in dry areas. Not recommended for damp areas.</b>
Solvent <b>Poor solvent resistance.</b>	Abrasion <b>NA</b>
Acid <b>NA</b>	Alkali <b>NA</b>

Typical Properties			
Gloss Level <b>0-3 at 60 degrees</b>	Thinner <b>Water</b>		
Colour <b>White</b>			
Components <b>1</b>			
Toxicity <b>Lead free. Dry film is non-toxic.</b>	V.O.C. Level <b>&lt; 40g/L (tinted or untinted)</b>		
Meets GBCA V.O.C. Requirements? <b>No</b>			
Touch Dry <b>20 Minutes</b>			
Clean Up  <b>Water</b>			
Clean Up Description Clean all equipment with water.			
Application Methods  <b>Air Spray</b>  <b>Airless Spray</b>  <b>Brush</b>  <b>Roller</b>			
Application Conditions	Solids by Volume		
	<input type="text" value="34.8"/>		
	Min	Max	Recommended
Wet Film Per Coat (microns)	<input type="text" value="66"/>	<input type="text" value="66"/>	<input type="text" value="66"/>
Dry Film Per Coat (microns)	<input type="text" value="23"/>	<input type="text" value="23"/>	<input type="text" value="23"/>
Recoat Time (min/hours)	<input type="text" value="2 Hours"/>	<input type="text" value="Indefinite"/>	<input type="text"/>
Theoretical Spread Rate (m <sup>2</sup> /L)	<input type="text" value="15.1"/>	<input type="text" value="15.1"/>	<input type="text" value="15.1"/>

Application Guide
<p><b>Surface Preparation</b></p> <p>All surfaces must be thoroughly cleaned and free of all loose dirt, dust, grease, loose or flaking paint, and loose surface plaster. Efflorescence or mould on masonry or concrete surfaces must be treated. Flatten gloss surfaces by thoroughly sanding and wipe clean with a damp cloth. For set plaster or plasterglass use a suitable sealer binder as a prep coat.</p>
<p><b>Application Procedure and Equipment</b></p> <p>Brush, roller, conventional and airless spray. Stir contents thoroughly before and during use with a broad flat stirrer using an upward lifting action.</p> <p><b>Brush/Roller:</b> Apply full even coats direct from container. If necessary, thin with up to 100 ml water per litre to assist application.</p> <p><b>Airless/Conventional Spray:</b> Suitable for application by all standard spray equipment. Up to 125 ml water per litre may be added to aid atomisation.</p>

Health and Safety	
<p>SDS Number <b>14543042, 0</b></p>	<p>SDS Link <a href="#">View SDS Link</a></p>
<p><b>Please refer to SDS Link. In case of emergency, please call 1800 220 770.</b></p>	

Transport and Storage	
<p>Pack A <b>671-70020</b></p>	
<p>Size: <b>2L, 4 L, 6L, 10L</b></p>	<p>Weight: <b>3.0Kg, 6.0Kg, 9.0Kg, 14.8Kg</b></p>
<p>Flash Point <b>NA</b></p>	<p>UN Number <b>NA</b></p>
<p>Dangerous Goods Class <b>NA</b></p>	<p>Package Group <b>NA</b></p>

**Disclaimer**

This Data Sheet is copyright to DuluxGroup (Australia) Pty Ltd and/or DuluxGroup (New Zealand) Pty Ltd (collectively, 'Dulux'). It may not be varied or altered without the prior written consent of Dulux, and if it is, Dulux has no responsibility or liability for those variations.

Unless Dulux has provided you with a customised, project-specific specification, this Data Sheet does not represent that any particular product or product system will be suitable for your project.

Any information provided in this Data Sheet is given in good faith and is believed by Dulux to be correct at the time of publication. Products and coating systems can be expected to perform as indicated in this Data Sheet, provided the substrate is in good condition, the coatings are applied by a suitably experienced and skilled applicator, and the preparation, application and maintenance is followed strictly as set out in this Data Sheet, and as recommended on the applicable Safety Data Sheets for the relevant products, available from [www.duspecplus.com.au](http://www.duspecplus.com.au). Climatic conditions at application time can affect product suitability and performance.

The correct colour or colour match is the responsibility of the applicator. Colours will change over time and Dulux does not guarantee that the same colour newly mixed will match a colour applied earlier which has been subjected to weathering or other change elements. No product colour is guaranteed against colour change.

Where any liability of Dulux in respect of this Data Sheet cannot by law be excluded, Dulux's liability is limited, as permitted by law and at Dulux's option, to resupply of the relevant products or services or to reimbursing the cost of those products or services.

WHERE LEAD MAY BE PRESENT: The asset manager is responsible for verifying the presence of lead and determining whether to remove or encapsulate the lead. If lead is present, the work must be done in strict accordance with AS 4361 Parts 1 and 2 and Worksafe Australia guidelines.