

AUBE00045 Berger Premium Water Based Enamel Gloss

Introduction

Part A
50870045

Description and Image

Berger Premium Water Based Enamel Gloss is suitable for use on all interior and exterior doors, windows, skirting boards and cupboards. It dries to a hard, durable finish.

Features and Benefits

- Rust resistant
- Quick drying
- Low odour
- Interior and Exterior Use

Uses

All interior and exterior doors, windows, architraves, skirting boards and cupboards.

✓ Interior ✓ Exterior

Precautions and Limitations





All preparation and painting must conform to AS 2311: The painting of buildings.

Do not paint at temperatures below 10C or when the surface temperature may fall below 10C during the drying period. Avoid exposure to steam and condensation for 48 hours after application. Although film is dry to touch after 30 minutes allow 7 days for film to cure before cleaning with a cloth, or soft brush with detergent solution.

Tinted colours Ensure that paint is thoroughly shaken and stirred immediately after addition of tinter to can and again before use.

Performance Guide

Weather Good resistance to weathering with a low level of chalking, colour change and dirt pick up	Salt NA
Heat Resistance Softens and sticks to other paint surfaces at over 70C	Water Suitable for use in wet areas such as bathroom doors, trim etc
Solvent Sensitive to aromatic hydrocarbons and alcohols.	Abrasion Marks and soiling easily removed
Acid NA	Alkali NA

Typical Properties			
Gloss Level Gloss	Thinner Water		
Components 1	Number of Coats 2		
Toxicity NA	V.O.C. Level <85		
Meets GBCA V.O.C. Requirements? No			
Touch Dry 20			
Clean Up  Water			
Clean Up Description Clean up all equipment in water.			
Application Methods  Air Spray  Brush  Roller			
Application Conditions	Solids by Volume <input type="text" value="32.87"/>		
	Min	Max	Recommended
Wet Film Per Coat (microns)	<input type="text" value="78"/>	<input type="text" value="78"/>	<input type="text" value="78"/>
Dry Film Per Coat (microns)	<input type="text" value="25"/>	<input type="text" value="25"/>	<input type="text" value="25"/>
Recoat Time (min/hours)	<input type="text" value="120"/>	<input type="text"/>	<input type="text" value="120"/>
Theoretical Spread Rate (m ² /L)	<input type="text" value="16"/>	<input type="text" value="16"/>	<input type="text" value="16"/>

Application Guide
<p>Surface Preparation</p> <p>All surfaces must be thoroughly cleaned and free of loose dirt, dust, grease, loose or flaking paint and loose surface plaster. Efflorescence or mould on masonry or concrete surfaces must be treated. Flatten gloss surfaces by thoroughly sanding and wipe clean with a damp cloth, then apply primer, sealer or undercoat as required.</p>
<p>Application Procedure and Equipment</p> <p>Brush roll or HVLP spray Stir contents thoroughly before and during use with a broad flat stirrer using an upward lifting action.</p> <p>Brush/Roll Apply evenly, ensuring to keep a wet edge whilst painting. Lay off with light vertical strokes. On wall areas use a 5-9mm nap roller to achieve the smoothest finish.</p> <p>Spray Application by HVLP spray suitable if thinned with 5% water.</p>

Health and Safety	
<p>SDS Number DLXGHSEN001118</p>	<p>SDS Link View SDS Link</p>
<p>Please refer to SDS Link. In case of emergency, please call 1800 220 770.</p>	

Transport and Storage	
<p>Pack A 50870045</p>	
<p>Size:</p> <div style="border: 1px solid black; padding: 2px; display: inline-block;"> <p>1L 2L 4L 10L</p> </div>	<p>Weight:</p> <div style="border: 1px solid black; padding: 2px; display: inline-block;"> <p>1.2Kg 2.4 Kg 4.8Kg 12 Kg</p> </div>

Disclaimer

This Data Sheet is copyright to DuluxGroup (Australia) Pty Ltd and/or DuluxGroup (New Zealand) Pty Ltd (collectively, 'Dulux'). It may not be varied or altered without the prior written consent of Dulux, and if it is, Dulux has no responsibility or liability for those variations.

Unless Dulux has provided you with a customised, project-specific specification, this Data Sheet does not represent that any particular product or product system will be suitable for your project.

Any information provided in this Data Sheet is given in good faith and is believed by Dulux to be correct at the time of publication. Products and coating systems can be expected to perform as indicated in this Data Sheet, provided the substrate is in good condition, the coatings are applied by a suitably experienced and skilled applicator, and the preparation, application and maintenance is followed strictly as set out in this Data Sheet, and as recommended on the applicable Safety Data Sheets for the relevant products, available from www.duspecplus.com.au. Climatic conditions at application time can affect product suitability and performance.

The correct colour or colour match is the responsibility of the applicator. Colours will change over time and Dulux does not guarantee that the same colour newly mixed will match a colour applied earlier which has been subjected to weathering or other change elements. No product colour is guaranteed against colour change.

Where any liability of Dulux in respect of this Data Sheet cannot by law be excluded, Dulux's liability is limited, as permitted by law and at Dulux's option, to resupply of the relevant products or services or to reimbursing the cost of those products or services.

WHERE LEAD MAY BE PRESENT: The asset manager is responsible for verifying the presence of lead and determining whether to remove or encapsulate the lead. If lead is present, the work must be done in strict accordance with AS 4361 Parts 1 and 2 and Worksafe Australia guidelines.