

AUDU00131 Dulux Stainless Steel Effect Effect

Introduction

Part A
690-D0104

Description and Image

Dulux Stainless Steel Effect gives a sleek, stylish stainless steel appearance to feature walls, architectural features and home accessories.
Available in 1 colour

Features and Benefits

- Gives a sleek, stylish stainless steel appearance
- Waterbased
- Interior only
- Washes up in water
- Ideal for feature walls, architectural features and home accessories





Uses

Dulux Stainless Steel Effect gives a sleek, stylish stainless steel appearance to interior feature walls, architectural features and home accessories.

✓ Interior ✓ Wall

Precautions and Limitations

Not suitable for high wear situations, wet areas or absorbent surfaces.
Temperatures must be above 10°C and below 30°C during application and drying.
Under cooler or more humid conditions allow longer drying times between coats.
Avoid exposure to steam and condensation for 48 hours.

Typical Properties			
Colour Light silvery grey. Available in one colour only.			
Components 1		Number of Coats 1	
V.O.C. Level <100 g/L			
Meets GBCA V.O.C. Requirements? No			
Touch Dry 30 minutes (at 25 Deg C and 50% relative Humidity)			
Clean Up  Water			
Application Methods  Air Spray  Brush  Roller			
Application Conditions			
	Min	Max	Recommended
Recoat Time (min/hours)	<input type="text" value="3 hours"/>	<input type="text"/>	<input type="text"/>
Theoretical Spread Rate (m ² /L)	<input type="text" value="12"/>	<input type="text" value="14"/>	<input type="text"/>

Application Guide

Surface Preparation

Ensure all surfaces are clean and dry prior to application. Brush down to remove dust.

Previously Painted Surfaces:

Wash down with sugar soap solution and rinse with clean water to remove any dirt, oil or grease. In cases where mould or mildew is present, use a household bleach solution. Dilute 1 part bleach with 3 parts clean water. Wear gloves and goggles. Use a scouring pad wet with bleach solution to lightly abrade the surface and ensure physical removal of stubborn areas of mould growth. Leave the bleach solution on the surface for 15 minutes, then thoroughly remove by washing down with clean water and wipe dry. In very severe cases, repeat this action to remove all mould.

Surfaces must be sanded to remove loose, peeling, flaking or chalky paint. Sand all gloss and semi gloss surfaces to a dull finish and wipe down with a damp cloth to remove surface dust. Apply one coat of Dulux Acrylic Sealer Undercoat or Dulux 1Step @ Acrylic Primer Sealer Undercoat to any areas that have been repaired or which have an uneven gloss level.

Bare Paper-faced Wallboard, Cement Sheet and Brick:

Brush down to remove any surface dust. Apply one coat of Dulux 1Step @ Acrylic Primer Sealer Undercoat or Dulux Acrylic Sealer Undercoat.

Bare Interior Timber:

Sand smooth. Dust off. Apply one coat of Dulux 1Step @ Acrylic Primer Sealer Undercoat.

Bare Set Plaster, Fibrous Plaster and Plasterglass:

Brush down to remove any surface dust. Apply one coat of Dulux Sealer Binder.

Metal:

Thoroughly degrease and apply Dulux All Metal Primer.
Allow 24 hours dry time prior to the application of Dulux Stainless Steel effect.

Application Procedure and Equipment

Stir thoroughly prior to use. Before you begin, test your chosen application method on a large piece of board. Mask off adjacent walls, skirting boards and cornices. Brush around the edges of the wall. Apply the first coat with a medium nap roller using light, even pressure. Take the roller as close to the edge as possible to cover the brush marks. Working in small sections, apply the second coat with a roller. While the paint is still wet, drag the brush in a random pattern. Best results are achieved by lightly brushing in one direction or reworking paint to achieve a brushed stainless steel effect. Make sure to overlap brushed areas to achieve an even effect. Avoid touching up.

Spraying: On broad wall areas application by spray is recommended as this will give a more authentic look. Thin with 5% water if required. Apply 3-4 thin coats to achieve the desired effect and coverage.

Thinning: Recommended for spraying only. Thin with 5% water.

Health and Safety

SDS Number
DLXGHSEN002634

SDS Link
[View SDS Link](#)

Using Safety Precautions
Keep out of reach of children. Use only in well ventilated areas. Wash hands after use.

Please refer to SDS Link. In case of emergency, please call 1800 220 770.

Transport and Storage	
Pack A 690D0104	
Size: <input type="text" value="250mL, 1L"/>	Weight: <input type="text" value="376g, 1.4kg"/>
Flash Point NA	UN Number NA
Dangerous Goods Class Not classified as Dangerous Goods for transport by Road & Rail and Marine, Not classified as Dangerous Goods for transport by Air.	

Disclaimer

This Data Sheet is copyright to DuluxGroup (Australia) Pty Ltd and/or DuluxGroup (New Zealand) Pty Ltd (collectively, 'Dulux'). It may not be varied or altered without the prior written consent of Dulux, and if it is, Dulux has no responsibility or liability for those variations.

Unless Dulux has provided you with a customised, project-specific specification, this Data Sheet does not represent that any particular product or product system will be suitable for your project.

Any information provided in this Data Sheet is given in good faith and is believed by Dulux to be correct at the time of publication. Products and coating systems can be expected to perform as indicated in this Data Sheet, provided the substrate is in good condition, the coatings are applied by a suitably experienced and skilled applicator, and the preparation, application and maintenance is followed strictly as set out in this Data Sheet, and as recommended on the applicable Safety Data Sheets for the relevant products, available from www.duspecplus.com.au. Climatic conditions at application time can affect product suitability and performance.

The correct colour or colour match is the responsibility of the applicator. Colours will change over time and Dulux does not guarantee that the same colour newly mixed will match a colour applied earlier which has been subjected to weathering or other change elements. No product colour is guaranteed against colour change.

Where any liability of Dulux in respect of this Data Sheet cannot by law be excluded, Dulux's liability is limited, as permitted by law and at Dulux's option, to resupply of the relevant products or services or to reimbursing the cost of those products or services.

WHERE LEAD MAY BE PRESENT: The asset manager is responsible for verifying the presence of lead and determining whether to remove or encapsulate the lead. If lead is present, the work must be done in strict accordance with AS 4361 Parts 1 and 2 and Worksafe Australia guidelines.