

Intergrain UltraPrep Tannin & Oil Remover

AU_DW02615

Part A	552W0103
--------	----------

Description

Intergrain UltraPrep™ Tannin & Oil Remover is a powerful, high strength remover. Specially formulated to quickly draw out tannins and oils from the surface of exterior timber. The high strength formula also lifts old or worn existing timber finishes.

Note: Intergrain UltraPrep Tannin & Oil Remover is not a paint and varnish stripper, to remove sound coatings use a coatings stripper or sand off.

Features

- High strength
- Draws out tannins and oils from the timber surface
- Lifts old or worn existing timber finishes


Uses

On all exterior timber including decking, outdoor furniture, cladding, screening and fences.
Not suitable for interior applications.

Precautions And Limitations

Exterior use only. Not suitable for interior use.
Wear waterproof gloves and safety glasses.
Avoid contact with painted, glass, concrete or metal surfaces and vegetation. Protect areas not to be cleaned.
May be corrosive to metals. Rinse off thoroughly if contact occurs.
You must always use UltraPrep Timber Cleaner after UltraPrep Tannin & Oil Remover.

Typical Properties

V.O.C. Level	<5g/L	Meets GBCA VOC Requirement?	Yes. Total Volatile Organic Content (TVOC) values are calculated in accordance to the stated methodology within Green Star Technical Manuals. The TVOC content is theoretically calculated as the sum total of the known VOC values of the product's raw material components. These materials include the base paint plus additional low VOC tinter required for non-factory packaged colours.
Clean Up	 Water		
Application Method	Other: Stiff bristle brush.		
Application Conditions	Min	Max	Recommended
	Wet Film Per Coat (microns)		
	Dry Film Per Coat (microns)		
	Recoat Time (min)		
	Theoretical Spread Rate (m ² /L)	10	
Typical Properties Notes	Use undiluted. COVERAGE Up to 10m ² /L		

Application Guide	
Surface Preparation	<ul style="list-style-type: none"> Remove surface dirt by sweeping or washing down with water.
Application Procedure And Equipment	<ul style="list-style-type: none"> Shake Intergrain UltraPrep Tannin & Oil Remover thoroughly. Wet the timber surfaces to be cleaned with water. Apply Intergrain UltraPrep Tannin & Oil Remover undiluted to the timber with a stiff bristle brush. Spot cleaning should be avoided to prevent patchy results. <p>Note: Product is very slippery, take care when walking on treated surface.</p> <p>Leave Intergrain UltraPrep Tannin & Oil Remover on the timber for 10–15 minutes. If necessary, apply more product to keep timber damp throughout this period. Do not allow to dry on the surface. Scrub the timber vigorously with a stiff broom. Do not use a wire brush. Rinse off exterior surfaces thoroughly using maximum pressure from a garden hose or using a high pressure water cleaner. For best results, a high pressure water cleaner is recommended. Important: Failure to thoroughly remove Intergrain UltraPrep Tannin & Oil Remover may result in timber discolouration under clear finishes. If removing worn coatings and stubborn areas remain, sand or repeat application as per the instructions above. Clean timber with Intergrain UltraPrep Timber Cleaner closely following label instructions</p> <p>Note: After cleaning with Intergrain UltraPrep Tannin & Oil Remover, some timber species will appear darker. Intergrain UltraPrep Timber Cleaner will restore brightness.</p> <p>Caution: Wear waterproof gloves and safety glasses.</p> <p>HELP & ADVICE Australia – 1800 630 285 www.intergrain.com.au</p> <p>NZ – 0800 222 687 www.intergrain.co.nz</p> <p>For detailed project specifications or a Safety Data Sheet, contact Intergrain Help & Advice or visit our website.</p>

Health And Safety			
Using Safety Precautions	CAUSES SEVERE SKIN BURNS AND SERIOUS EYE DAMAGE. MAY CAUSE RESPIRATORY IRRITATION Do not breathe fume, mist, vapours or spray. Use only outdoors or in a well-ventilated area. Wear protective clothing, gloves, eye/face protection and a suitable respirator as required. Wash contaminated clothing before reuse. Wash hands, face and all exposed skin thoroughly after handling. Keep container tightly closed. Store locked up. Store in a well ventilated place, away from foodstuffs, oxidising agents and acids. Do not empty into drains. Slippery when spilt	Health Effects	SEE THE SAFETY DATA SHEET FOR ADDITIONAL INFORMATION. EMERGENCY INFORMATION (ALL HOURS): AUST – 1800 033 111; NZ – 0800 734 607. FIRST AID: If poisoning occurs, contact a Doctor or Poisons Information Centre (Phone Australia 131 126; New Zealand 0800 764 766). If medical advice is needed, have product container or label at hand. SWALLOWED: If swallowed, rinse mouth. Do NOT induce vomiting. Give a glass of water. Immediately call a POISON CENTRE or doctor/physician. EYE: If in eyes, hold eyes open, flush with running water. Continue flushing until advised to stop by a Poisons Information Centre or a doctor, or for at least 15 minutes and see a doctor. SKIN: If skin or hair contact occurs, immediately remove any contaminated clothing and wash skin and hair thoroughly with running water. If swelling, redness, blistering or irritation occurs seek medical assistance. For skin burns, cover with a clean, dry dressing until medical help is available. INHALED: Remove from contaminated area – avoid becoming a casualty. Allow patient to assume most comfortable position and keep warm. Apply artificial respiration if not breathing. Seek medical advice.
Flammability	Non-flammable.	Fire Suppression	If involved in a fire use water fog, foam or dry agents. Avoid breathing products of combustion. For Spills & Disposal: Clear area of all unprotected
Protective Equipment	Wear waterproof gloves and safety glasses.	Storage	Keep out of reach of children. Keep container tightly closed. Store locked up. Store in a well ventilated place, away from foodstuffs, oxidising agents and acids.
Disposal	Dispose of contents/container in accordance with local, regional, national and international regulations.	Other	CONTAINS: 1-10% Alkaline Salts
In the case of emergency, please call 1800 033 111			

Transport And Storage	
Pack A	552W0103
Size	Weight
1L	1.14
4L	4.39
10L	11.23

Disclaimer

Dulux, Selleys and Other marks followed by ® are registered trademarks. Marks followed by the symbol of ™ are trademarks.

The data provided within the Duspec system is correct at the time of publication, however it is the responsibility of those using this information to check that it is current prior to specifying or using any of these coating/product systems.
DISCLAIMER: Any advice, recommendation, information, assistance or service provided by any of the divisions of DuluxGroup (Australia) Pty Ltd or its related entities (collectively, DuluxGroup) in relation to goods manufactured by it or their use and application is given in good faith and is believed by DuluxGroup to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by DuluxGroup is provided without liability or responsibility PROVIDED THAT the foregoing shall not exclude, limit, restrict or modify the right entitlements and remedies conferred upon any person or the liabilities imposed upon DuluxGroup by any condition or warranty implied by Commonwealth, State or Territory Act or ordinance void or prohibiting such exclusion limitation or modification. Coating/product systems can be expected to perform as indicated on the Duspec Spec Sheet so long as applications and application procedures of the individual products are followed as recommended on the appropriate Product data Sheet. "DuluxGroup" "Dulux" "Selleys" "Berger" "Berger Gold Label" "Hadrian" "Walpamur" "Levene" "Acratex" and Other marks followed by ® are registered trademarks of DuluxGroup (Australia) Pty Ltd ABN 67 000 049 427. Marks followed by the symbol ™ are trademarks.

Please note that this document is only valid for 60 days from the date of issue.

DuluxGroup (Australia) Pty Ltd 1956 Dandenong Road, Clayton, Victoria 3168 AU ABN 67 000 049 427