

No More Gaps® Exterior

Description

Selleys No More Gaps Exterior is the ideal solution for filling gaps and cracks around and between weatherboards, eaves, and exterior windows & doors. It has been formulated with a unique polymer system for superior flexibility in exterior applications and using a titanium compound to protect against UV and weather damage.

Product Information

Packaging	Size	Colour
Cartridge	430g	White

Uses

- Suitable for use on:
- Timber weatherboard
- Synthetic weatherboard
- FC sheet
- Brick
- Masonry
- Aluminium

Features

- High flexibility
- UV resistant
- Superior weather protection
- Mould resistant
- Water clean up
- Paintable

Technical Details

Property	Typical Result
Technology	Water-based
Colour	White
Density	1.45 ± 0.05
Application Temperature	5 to 40°C
Skin Time	30 ± 5 minutes
Tack-Free Time	45 ± 5 minutes
Tensile Strength	0.6 ± 0.05Mpa
Shore A Hardness	> 40
Elongation at Break	500% (ASTM D412)
Modulus at 100% Elongation	0.5 ± 0.1
Movement Capability	+/-25% (ISO 9046)
Indicative data only, not intended for preparation of specifications	

Surface Preparation

Surface must be clean, dry and free from dust, grease, flaking/powdery paint and old or crumbling caulk.

Directions for Use

1. Ensure surfaces are clean, dry and free from dust or grease.
2. Cut nozzle at 45° angle, cut cartridge tip and fit nozzle. Insert cartridge into caulking gun.
3. Apply with caulking gun, pushing product into gap or joint.
4. Smooth out with a wet spatula, ensuring sufficient product remains in joint.
5. Clean up wet product with a damp cloth immediately.
6. Allow surface to skin prior to painting (approx. 30minutes*).
7. To allow product to strengthen, protect from water for 24 hours.

Tips

- For new weatherboard, check manufacturer's instructions before using this product.
- *To avoid paint cracking, apply to gaps (no larger than 5mm deep and 10mm wide) at temperatures above 10°C. Allow sealant to dry before painting over. Avoid applying paint too thickly. Allow 24-48 hours before painting with oil-based paints. Longer drying times are required for flat and ceiling paints because they are highly filled (i.e. contains lower binder content than other paints). This means the paint does not flex as much when the sealant dries.
- For maximum durability on bare exterior surfaces, apply a coat of acrylic paint and allow to dry before applying this product. Always paint over with a quality exterior paint.
- Note that in harsh conditions, joints between boards may expand beyond product's movement capability; in such cases, re-apply product and paint over.

Clean Up

Clean up excess caulk with water using a damp cloth before it dries.

Cured caulk will need to be cut; remaining caulk can be softened with acetone and then removed.

No More Gaps[®] Exterior

Storage

Store in a cool, dry, well-ventilated place and out of direct sunlight. Store away from foodstuffs.

Limitations

- Maximum gap size recommended:
Width: 10mm / Depth: 5mm.
- Not for sealing around bathtubs, kitchen sinks, etc. use No More Gaps Bathroom & Kitchen.
- Use the appropriate Selleys Silicone Sealant where excessive joint movement occurs or for areas prone to frequent water immersion.
- Not to be stored or applied below 10°C

Warnings, First Aid and Shipping Information

This information can be located on the product SDS found through our website – www.selleys.com