

Selleys No More Gaps Interior Multipurpose

Description

Selleys No More Gaps Interior Multipurpose is an easy to use gap filler ideal for filling gaps and cracks around skirting boards, cornices and inside window and door frames. The water-based formulation has been designed to cope with building movement to ensure a long lasting and crack resistant finish.

Indicative data only, not intended for preparation of specifications

Product Information

Packaging	Size	Colour
Cartridge	475 g	White

Uses

Suitable for use on plasterboard, wood, particle board, cement sheeting, aluminium and glass.

Features

- Long Lasting
- Crack Resistant Finish
- Paintable
- Flexible
- Low Shrink

Technical Details

Property	Typical Result
Technology	Water-based
Colour	White
Density	1.64
Sag Resistance (inches)	0.05 (maximum)
Skin Time (23°C, 50% Humidity)	20 minutes
Peel Strength (Anodised Aluminium,)	+ 50 N
Shore A Hardness (Cured sealant)	68
Elongation at Break (ASTM D412)	+300%
Modulus at 100% Elongation (ASTM D412)	0.35 MPa
Movement Capability ISO 9046	Up to 20%
Shelf Life (un-opened cartridge)	24 Months

Directions for Use

1. Ensure surfaces are clean, dry and free from dust or grease.
2. Cut nozzle at 45° angle, cut cartridge tip and fit nozzle. Insert cartridge into caulking gun.
3. Apply with caulking gun, pushing product into gap or joint.
4. Smooth with a wet gloved finger/spatula.
5. Clean up: Wet – Clean up using a damp cloth.
Dry – Clean up using scraper.
6. Allow surface to skin prior to painting (approx. 30 minutes*)

Tips

Suitable for exterior applications.

*To avoid paint cracking apply to gaps (no larger than 5mm deep and 10 mm wide) at a temperatures above 10 °C. Allow sealant to dry before painting over. Avoid applying paint too thickly. Allow 24-48 hours before painting with oil based paints. Longer drying times are required for flat and ceiling paints because they are highly filled (i.e. contains lower binder content than other paints.) This means the paint does not flex as much when the sealant dries.

Coverage

One cartridge will produce a 6mm bead of sealant approximately 10.4 metres long

Storage

For maximum shelf life, the product should be kept sealed and in a cool, place out of direct sunlight. Store product above 5 °C

Limitations

- Do not apply or store below 5 °C.

Selleys No More Gaps Interior Multipurpose

- Not suitable for permanent water immersion or in constantly damp areas.
- Not suitable for gaps between tongue and groove boards or weatherboards. For these, use No More Gaps Exterior.

Warnings, First Aid and Shipping Information

This information can be located on the product SDS found through our website – www.selleys.com